

Aten RS42U120 42U RS Series Standing Network Rack (2055mm x 600mm x 1200mm)

Physical Properties	
Rack Height (U Spaces)	42U
Type	Rack Enclosure
Package Contents	"Build-Up(Default) Knock-Down(Special Requirement) "
Mounting Hole Type	Square
Color	Black
Unit Dimensions(H*W*D)	2055 x 600 x 1200
Maximum Device Height	2055
Maximum Device Width	600
Maximum Device Depth	1200
Max/Min/Default Mounting	1190/200/900
Maximum Mounting	1190
Minimum Mounting	200
Default Mounting	900
Shipping DimensionsBuild-Up (H x W x D)	620 x 1220 x 2065
Shipping DimensionsKnock-Down (H x W x D)	"Package1 : 1980 x 620 x 320 Package2 : 620 x 1220 x 130 Package3 : 1910 x 60 x 730
Shipping Weight	112
Unit weight	107
Weight capacity stationary	800
Weight capacity dynamic	600
Material	SPCC Cold Rolled Steel
Air permeability	0.65
Certifications	
Approvals	CE
Certifications	RoHS
Protection class	IP20
Shipping	
Build-Up packing Unit volume (CBM)	1.71
Knock-Down packing Unit volume (CBM)	Package1 : 0.39 Package2 : 0.10 Package3 : 0.08
Build-up package (20GP)	13
Build-up package (40GP)	28
Build-up package (40HQ)	28
Knock-Down package (20GP)	46
Knock-Down package (40GP)	95
Knock-Down package (40HQ)	113
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.