

## Aten RS22U80 22U RS Series Standing Network Rack (1166mm x 600mm x 800mm)

Physical Properties	
Rack Height (U Spaces)	22U
Type	Rack Enclosure
Package Contents	"Build-Up(Default) Knock-Down(Special Requirement) "
Mounting Hole Type	Square
Color	Black
Unit Dimensions(H*W*D)	1166 x 600 x 800
Maximum Device Height	1166
Maximum Device Width	600
Maximum Device Depth	800
Max/Min/Default Mounting	690/200/500
Maximum Mounting	690
Minimum Mounting	200
Default Mounting	500
Shipping DimensionsBuild-Up ( H x W x D)	620 x 820 x 1180
Shipping DimensionsKnock-Down ( H x W x D)	Package1 : 1100 x 620 x 320 Package2 : 620 x 620 x 130
Shipping Weight	80
Unit weight	60
Weight capacity stationary	800
Weight capacity dynamic	600
Material	SPCC Cold Rolled Steel
Air permeability	0.65
Certifications	
Approvals	CE
Certifications	RoHS
Protection class	IP20
Shipping	
Build-Up packing Unit volume (CBM)	0.60
Knock-Down packing Unit volume (CBM)	Package1 : 0.22 Package2 : 0.05
Build-up package (20GP)	25
Build-up package (40GP)	50
Build-up package (40HQ)	100
Knock-Down package (20GP)	95
Knock-Down package (40GP)	200
Knock-Down package (40HQ)	230
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.