

Kramer RC-308/US-D(W/B) US-D Size 8-Button Control Keypad with White/Black 1-Gang DECORA Design Frame

INPUTS

- 1 IR Sensor: For IR learning

OUTPUTS

- 2 IR: On 2-pin terminal block connectors
- 2 Relays: On 2-pin terminal block connectors (36V AC or DC, 2A, 60VAC maximum on non-inductive load)

PORTS

- 1 Ethernet: On an RJ-45 female connector for PoE, device configuration, control and firmware upgrade
- 2 RS-232: On 3-pin terminal block connectors
- 1 RS-485: On a 3-pin terminal block connector
- 1 K-NET: On a 4-pin terminal block connector
- 1 GPI/O: On a 2-pin terminal block connector
- 1 Mini USB: On a female mini USB-B connector for configuration and firmware upgrade

DEFAULT IP SETTINGS

- DHCP Enabled

POWER

- Source: PoE or 12V DC 2A power supply
- Consumption: 12V DC, 780mA

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

REGULATORY

- Safety: CE, UL
- Environmental: RoHs, WEEE

ENCLOSURE

- Size: 1 Gang wall plate
- Cooling: Convection ventilation

ACCESSORIES

- Included: 12V DC power adapter, special tweezers for removing button caps, standard button label set
- Optional: Extended button label set

PRODUCT DIMENSION

- EU: 8.00cm x 4.70cm x 8.00cm (3.15" x 1.85" x 3.15") W, D, H
- UK: 8.60cm x 4.70cm x 8.60cm (3.39" x 1.85" x 3.39") W, D, H
- US: 6.98cm x 4.70cm x 11.43cm (2.75" x 1.85" x 4.50") W, D, H

PRODUCT WEIGHT

- EU: 0.1kg (0.2lbs) approx.
- UK: 0.1kg (0.2lbs) approx.
- US: 0.1kg (0.2lbs) approx.

SHIPPING DIMENSION

- EU: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H
- UK: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H
- US: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

SHIPPING WEIGHT

- EU: 0.4kg (0.8lbs) approx.
- UK: 0.4kg (0.8lbs) approx.
- US: 0.4kg (0.8lbs) approx.