

# Kramer 7508 Multi-Standard Composite Video and S-Video to SDI Format Converter

## INPUTS

- 1 composite video, 1Vpp/75Ω on a BNC connector
- 1 s-Video, 1Vpp, 0.3Vpp/75Ω on a 4-pin connector

## OUTPUTS

- 2 SDI SMPTE-259M, ITU-R BT.601 on BNC connectors

## DIGITAL RESOLUTION

- 10 bits

## BANDWIDTH

- 5MHz (-0.2dB)

## SIGNAL TO NOISE RATIO

- 57dB

## K-FACTOR

- <0.2%

## DIFFERENTIAL PHASE

- 1Deg

## DIFFERENTIAL GAIN

- 1%

## LUMA NON-LINEARITY

- 1%

## CHROMA/LUMA DELAY

- <15ns

## CONTROL

- Brightness, contrast, hue, saturation, sharpness via RS-232

## POWER CONSUMPTION

- 12V DC, 210mA

## INCLUDED ACCESSORIES

- Power supply, mounting bracket

## OPTIONS

- RK-3T 19" rack adapter

## PRODUCT DIMENSION

- 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H

## SHIPPING DIMENSION

- 23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50" ) W, D, H

## SHIPPING WEIGHT

- 0.6kg (1.3lbs) approx.

## PRODUCT WEIGHT

- 0.2kg (0.4lbs) approx.