

A-NeuVideo ANI-VW 1x4 HDMI Video Wall Scaler Splitter with Looping Output (Cascadable)

- **Supported Input Formats:**
 - **HDMI:** 1080p@50/60Hz, 1080i@50/60Hz, 720p@50/60Hz, 576i/p,480i/p, 640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1360x768@60Hz, 1440x900@60Hz, 1680x1050@60Hz, 1920x1080@60Hz
 - **CVBS:** PAL, NTSC, SECAM with stereo audio input
 - **VGA:** 640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1360x768@60Hz, 1440x900@60Hz, 1680x1050@60Hz, 1920x1080@60Hz
 - **USB:** MPEG, H.264, RM/RMVB movie decode, JPEG, BMP, PNG Picture decode and MPEG1/2, MP3 audio decode
- **Input Ports:**
 - HDMI (Female type)
 - USB
 - VGA
 - CVBS+L/R
- **Output Ports:**
 - (5) HDMI (Female type)
 - Coaxial
 - (2) L/R
- **Video Bandwidth:** 225MHz/6.75Gbps
- **HDMI Cable Distance:** ~50ft/15M@8-bit 1080p
- **Power Supply:** 12V/2.5A DC (US/EU standards, CE/FCC/UL certification)
- **ESD Protection Human Body Model:**
 - ± 8kV (air-gap discharge)
 - ± 4kV (contact discharge)
- **Dimensions (WxDxH):** 9.9 x 4.6 x 1.25 in (250x118x32mm)
- **Weight:** 2.4 lbs /1050g
- **Chassis Material:** Metal
- **Silkscreen Color:** Black
- **Operating Temperature:** 0°C ~ 40°C / 32°F ~ 104°F
- **Storage Temperature:** -20°C ~ 60°C / -4°F ~ 140°F
- **Relative Humidity:** 20 ~ 90% RH (Non-condensing)
- **Power Consumption (Max):** 7.5W