

A-NeuVideo ANI-5MFS UHD 4K 60Hz Multi-Format Video Presentation Scaler Switch with Audio

- HDMI Compliance: HDMI 2.0b
- DP Compliance: Display Port 1.2a
- HDCP Compliance: HDCP 2.2 and HDCP 1.4
- Video Input Resolutions:
 - HDMI/Display Port: Up to 4K2K@50/60Hz (4:4:4)
 - CVBS: PAL/NTSC 3.58/NTSC 4.43/SECAM/PAL M/PAL N
 - YPBPR: 480i to 1080p
 - VGA: 640x480/60 to 1920x1200/60
- HDMI/HDBaseT™ Output Resolutions: 4K2K@30Hz, 4K2K@25Hz, 1920x1080p@60Hz, 1920x1080p@50Hz, 1280x720p@60Hz, 1280x720p@50Hz, 1024x768@60Hz, 1280x800@60Hz, 1360x768@60Hz, 1400x1050@60Hz, 1680x1050@60Hz, 1920x1200@60Hz
- Audio Formats: LPCM 2.0CH
- ESD Protection: Human body model: $\pm 8\text{kV}$ (air-gap discharge) & $\pm 4\text{kV}$ (contact discharge)
- Input Ports:
 - (3) HDMI Type A (19-pin female)
 - Display Port (female)
 - VGA (female)
 - MIC Input (3-pin phoenix port)
 - (5) Stereo inputs (3-pin phoenix port)
- Output Ports:
 - HDMI Output Type A (19-pin female)
 - HDBaseT™ Out (RJ-45)
 - Stereo Output (3-pin phoenix port)
- Control Interfaces:
 - IR In (3.5mm mini jack)
 - IR Out (3.5mm mini jack)
 - Contact In (6-pin phoenix port)
 - RS-232 (3-pin phoenix port)
 - Web GUI (RJ-45)
 - USB Type A (5-pin female)
- Dimensions (WxDxH): 5.9 x 8.7 x 1.7 in (150x220x44mm)
- Weight: 2.75lb/1250g
- Housing: Metal / Black
- Operating Temperature: $0^{\circ}\text{C}\sim 40^{\circ}\text{C}/32^{\circ}\text{F}\sim 104^{\circ}\text{F}$
- Storage Temperature: $-20^{\circ}\text{C}\sim 60^{\circ}\text{C}/-4^{\circ}\text{F}\sim 140^{\circ}\text{F}$
- Relative Humidity: 20~90%RH (non-condensing)
- Power Consumption: 9W (Main unit) / 18W (Main unit + HDBaseT™ Receiver)
- Power Supply: DC 24V/1A Adaptor (US/EU standards, CE/FCC/UL certified)