

Gefen EXT-UHD600A-88 4K Ultra HD HDMI 600 MHz 8x8 Matrix Switcher

- Maximum TMDS Clock: 600 MHz
- Total Signal Bandwidth/Data Rate: 18 Gbps
- HDMI Input Connectors: (8) Type A 19-pin female, locking
- HDMI Output Connectors: (8) Type A 19-pin female, locking
- Digital Audio Output Connectors: (8) TOSLINK® Optical, (8) RCA Coaxial
- Analog L/R Audio Output Connectors: (8) 3.5mm mini-stereo jack
- RS-232 serial port: (1) DB-9, female
- Ethernet (IP Control) Port: (1) RJ-45
- Display: OLED, 2 rows, 20 characters per row
- Power Button/Indicator: (1) tact-type, bi-color blue/orange backlight
- Control Buttons/Indicators: (9) tact-type
- Reset Button: (1) tact-type, recessed
- IR Sensor: (1), located on front panel
- IR In/Ext Port: (1) 3.5mm mini-stereo jack
- IR Extender type: EXT-RMT-EXTIRN (not included)
- DC Power Connector: (1) 4-pin, locking
- Power Supply: 24V DC
- Power Consumption: TBD45W
- Operating Temperature: +32 to +122 °F (0 to +50 °C)
- Operating Humidity: 5% to 90% RH, non-condensing
- Storage Temperature: -4 to +140 185 °F (-20 to +60 85 °C)
- Storage Humidity: 50% to 95% RH, non-condensing
- MTBF: TBD50000 hours
- Rack mounting requirements: Standard 19" rack, 2U high
- Dimensions (excluding rack ears and connectors, W x H x D):
 - 17.25" x 3.5" x 15.75" (440mm x 89mm x 400mm)
- Net Unit Weight: 21 lbs. (9.6 kg)
- Shipping Weight: 29 lbs. (13.25 kg)