

KanexPro EXT-HDBT70C 4K/30 HDMI Extender (Transmitter/Receiver) Set over HDBaseT

Transmitter:

Input Signal

- (1) HDMI, (1) IR; (1) RS232

Input Connector

- (1) HDMI female; (1) 3.5mm mini jack;
- (1) 3p captive screw connector

Output

- (1) RJ-45, (1) IR, (1) RS232

Output Connector

- (1) RJ-45; (1) 3.5mm mini jack;
- (1) 3-pin captive screw connector

Audio

- (1) Digital audio, transmit through HDMI audio

Receiver:

Input Signal

- (1) IR; (1) RJ-45; (1) RS232

Input Connector

- (1) 3.5mm mini jack; (1) RJ-45; (1) 3p captive screw connector

Output

- (1) HDMI
- (1) IR
- (1) RS232

Output Connector

- (1) HDMI female
- (1) 3.5mm mini jack
- (1) 3-pin captive screw connector

General

Resolution Range:

- 640x480@60Hz~4Kx2K@30Hz

Transmission Mode

- HDBaseT

Transmission Distance

- 1080p ≤ 70m; 4Kx2K ≤ 40m

Bandwidth: 10.2Gbps

HDMI Standards - Supports HDMI1.4 and HDCP2.2

Impedance: 75Ω

Temperature: 0~ 50 C

Humidity: 10% ~ 90%

External Power Supply

- Input: 100VAC~240VAC, 50/60Hz;
- Output: DC 24V, 1.25A

Power Consumption

- 14w (max)

Dimensions (W*H*D): 4.17' x 0.60" x 3.30"

Net Weight: 0.55 lbs (250g)