

KanexPro SW-HDSC914K 9-Input DisplayPort/HDMI/VGA Scaler/Switcher with 4K HDBaseT

Video	
Video Input	(1) HDBaseT, (1) DisplayPort, (5) HDMI, (2) VGA
Video Input Connector	(1) RJ45, (1) Female DisplayPort, (5) Type A HDMI (2) 15-pin Female VGA
Video Output	(1) HDMI & (1) HDBaseT (PoH)
Video Output Connector	(1) Type A HDMI; (1) RJ45
Output Resolution	1280x720 (default), 1920x1080, 1024x768 3840x2160@30Hz, 3840x2160@60Hz
Standards	Input video support: HDMI 2.0 & HDCP2.2 Output video support: HDMI 2.0 & HDCP1.4
Audio	
Audio Input	(1) Stereo audio input for 2-DP, (1) Stereo audio input for 3-HDMI, (2) Stereo audio inputs for 8-VGA and 9-VGA, (1) LINE Audio & (1) MIC Audio
Audio Input Connector	(4) 3.5mm Stereo Jacks & (2) 3-pin Phoenix Connectors
Audio Input Impedance	>10kΩ
Audio Output	1) Dual-Mono Analog Audio (1) Power Amplifier with Fixed Voltage
Audio Output Connector	(1) 5-pin Phoenix Connector, (1) 3-pin Phoenix connector
Audio Output Impedance	70Ω
Frequency Response	20Hz~20K Hz
Stereo Channel Separation	>80dB @1KHz
Control Part	
Control Port	(1) USB firmware port, (1) IR eye, (1) IR All IN, (1) IR ALL OUT, (3) RS232, (1) TCP/IP
Control Connector	(1) Type-A USB, (3) 3.5mm Mini Jacks, (3) 3-pin Phoenix Connectors, (1) RJ45
General	
Transmission Distance	HDBaseT Input: 1080p=70m, 4Kx2K=40m HDBaseT Output: 1080p=100m, 4Kx2K=70m.
Operation Temperature	0 ~ +40C
Storage Temperature	-10 ~ +55C
Relative Humidity	10% ~ 90%
External Power Supply	100V~240V AC
Power Consumption	45W (Max)
Dimensions (W x H x D)	17.0"W x 1.70"H x 11.0"D
Net Weight	7.0 lbs. (3.17 Kg)