

KanexPro EXT-HDBT150M HDMI 150m Extender (Transmitter/Receiver) Kit over HDBaseT with loop out

Connections:

Inputs:

Transmitter:

- 1 x HDMI Type A (19-pin female)
- 1 x HDMI Type A (19-pin female) - For loop or local output
- 1 x IR INPUT (3.5mm Stereo Mini-jack)
- 1 x RS232 (Phoenix connector)

Receiver:

- 1 x HDBaseT in (RJ45)
- 1 x IR INPUT (3.5mm Stereo Mini-jack)
- 1 x RS232 (Phoenix jack)

Outputs:

Transmitter:

- 1 x HDBaseT Out (RJ45)
- 1 x HDMI Type A (19-pin female)
- 1 x IR OUTPUT (3.5mm Stereo Mini-jack)

Receiver:

- 1 x HDMI Type A (19-pin female)
- 1 x IR OUTPUT (3.5mm Stereo Mini-jack)

Compliance:

- HDMI Compliance: HDMI 1.4
- HDCP Compliance: HDCP 1.4
- Video Bandwidth: 225MHz per channel
- Video Resolutions up to: 1080p@60Hz, YUV4:4:4, RGB4:4:4
- Color Space: RGB, YUV4:4:4, YUV 4:2:2
- Color Depth: 8-bit

HDMI Audio Formats (Pass-through):

- LPCM 2/5.1/7.1CH, Dolby Digital
- DTS 5.1, Dolby Digital+, Dolby True HD
- DTS-HD Master Audio
- Dolby Atmos
- DTS:X

Mechanical:

- Chassis: Metal Enclosure
- ESD Protection - Human body model:
- ±8kV (air-gap discharge)
- ±4kV (contact discharge)
- Color: Black
- Dimensions: W: 5.51" x H: 2.55" x D: 0.70"
- Weight: 0.89 lbs. (406g)

Power & Temperature

- Power Supply Input: AC100 - 240V 50/60Hz
- Output: DC 24V/1A (US/EU standards, CE/FCC/UL Certified)
- Power Consumption: 6W

- Operating Temperature: 32 - 104°F / 0 - 40°C
- Storage temperature -4 - 140°F / -20 - 60°C
- Relative Humidity 20 - 90% RH (no condensation)