

KanexPro CR-3XCONTROL Integrated IR/RS-232 and Relay Controller

Input Ports	1xIR Learner/Extender (3.5mm), 8xTrigger (10-pin TerminalBlock)
Output Ports	4xIR Blaster (3.5mm), 4xRelay(2-pinTerminal Block), 1xCOM (5-pinTerminal Block)
Control Interfaces	1xIP Control(RJ45)
IR Frequency	30 - 50kHz (30 - 60kHz underideal conditions)
Baud Rate	Up to115200bps
Power Supply	5V/2.6A DC (US/EU standards,CE/FCC/UL certified)
ESD Protection	Human BodyModel: ±12kV (AirDischarge) ±8kV (ContactDischarge)
Dimensions	<ul style="list-style-type: none"> • 5.0" x 0.98"x 4.25" WHD • (128mmx25mmx108mm) • CaseOnly: 5.0"x0.98"x4.64" 128mmx25mmx118mm(WHD) (All Inclusive)
Weight	0.88 lbs. (400g)
Chassis Material	Metal
Color	Black
Operating Temperature	0°C - 40°C/32°F -104°F
Storage Temperature	-20°C - 60°C/-4°F -140°F
Relative Humidity	20 - 90% RH(Non-condensing)
Power Consumption	3.63W