

WyreStorm EX-SW-0201-4K HDBaseT VGA/HDMI Extender (Transmitter/Receiver) Set/PoH

Supporting resolutions up to 4K, this fully-featured Class A HDBaseT extender is designed for use in small meeting room or classroom environments where distribution and control of VGA or HDMI devices up to 100m/328ft is required.

Features:

- A full-featured HDBaseT™ extender set with the added feature of a VGA/ HDMI auto-switching transmitter
- Transmits HD resolutions up to 1920x1200 to 100m/328ft
- Transmits 4K@60Hz (4096x2160) to 70m/230ft
- Auto-switching transmitter detects and selects VGA (+audio) and HDMI devices as soon as the source is connected
- 2-way PoH gives flexible installation options by allowing either the transmitter or receiver to be powered remotely
- Audio embed on transmitter and audio de-embed on receiver via 3.5mm jack connection for HDMI or VGA
- HDCP 2.2 compliant
- EDID management and DIP switch selection for manual setting of resolution, RS-232 control/firmware update function and long cable mode
- Low-profile 18mm chassis for unobtrusive installation
- Cable termination follows IEEE-568B standards
- LED indication for power supply to units, signal status to show established display connection, HDCP presence in signal and transmission link.
- Threaded bushings allow use of both standard and locking DC power plugs
- Energy efficient universal power supply included
- Mounting brackets included