

WyreStorm SW-0401-HDBT 4x1 HDMI/Display Port/VGA over HDBaseT Presentation Switcher Scaler with CEC Control

Slotting in neatly between our existing SW-0201-4K and the SW-0501-HDBT presentation switchers, the SW-0401-HDBT is a scaling, multi-format 4-to-1 switcher for huddle rooms and meeting spaces featuring VGA + stereo audio, DisplayPort and dual HDMI Inputs to a single Class A HDBaseT and mirrored HDMI Outputs.

All inputs can be switched automatically or manually, with HDMI Inputs able to be scaled up to 4K/30 UHD from both HDMI and HDBaseT Outputs.

Balanced audio breakout allows connection to a local audio system and CEC power triggers can be sent to compatible screens to turn on/off sink devices by auto-detecting source status.

Boasting DisplayPort within its 4 input options, as well as balanced audio breakout and scaled Class A HDBaseT and HDMI outputs, the SW-0401-HDBT represents a powerful solution for increasingly common huddle and meeting space applications within corporate and education environments.

Features:

- 4-input smart presentation switch with dual, scaled outputs
- Mirrored HDMI out with up to 4K@30Hz scaler and balanced audio output
- Class A HDBaseT for transmission of 4K video, audio, Ethernet, power and control signals
- Supporting transmissions distances of 4K/30Hz to 70m/230ft and 1080p to 100m/328ft
- CEC controller built in to turn on/off sink device by auto-detecting source status
- Automatically switches between VGA, DisplayPort and two HDMI inputs
- 1x VGA+3.5mm stereo up to 1920x1200@60Hz, 1x DisplayPort and 2x HDMI inputs up to 3840x2160@30Hz
- Mirrored HDMI and HDBaseT outputs scales output to 4K
- DIP switch provided to adjust automatic or manual switching mode
- Rotary switch provided to adjust between auto-scaler and forced output resolutions
- RS-232, front panel and CC control (+ LED) of switching
- Contact closure points provided to switch sources or turn on/off sink device
- Auto-switching based on power state and last connected source - switches to the latest source when all inputs are connected or any input disconnected
- PoH HDBaseT output powers RX-70-4K or RX-70-4K-ARC receivers at screen or projector location
- Active CEC technology ensures display devices are in correct power state depending if sources are being used