

Avenview DVI-SPLITPRO-2X DVI Dual Screen MultiViewer w Rotation/Chromakey

ITEM	DESCRIPTION
UNIT	DVI-SPLITPRO-2X
UNIT DESCRIPTION	Advanced Dual Screen Video Processor with Front Panel and IR Control
DUAL OUTPUT SUPPORT	Yes (DVI & HDMI)
BACKGROUND VIDEO INPUT	Yes
HDCP COMPLIANCE	Yes
VIDEO BANDWIDTH	DVI [Single-link 4.95Gbps] HDMI [2.25G to 6.75Gbps]
SUPPORTED RESOLUTIONS	480i / 480p / 720p / 1080i / 1080p (60) / 1920x1200@75 / 1600x1200@60
AUDIO SUPPORT	No
CONTROL	RS232 / IP Control
EMBEDDED VIDEO MIXER	Yes
ABILITY TO CASCADE	Yes
INPUT TMDS SIGNAL	1.2 Volts (peak – peak)
ESD PROTECTION	Human body model - ± 15kV (air gap discharge) & ±8kV (contact discharge)
INPUT	2x DVI/HDMI
	2x RS-232
	1x RJ-45
OUTPUT	2 x DVI (Also supports HDMI 1.2 signal by DVI to HDMI Cable)
DVI CONNECTOR TYPE	DVI-I (29-Pin female)
RS232 CONNECTOR	DE-9 (9-pin D-sub female)
RJ45 CONNECTOR	WE/SS 8P8C with 2 LED indicators
DIMENSIONS	10.3" x 7.6" x 1.7" (L x W x H)
WEIGHT	6.4 lbs
SIZE	1U Rack-mount with ears
POWER SUPPLY	AC 100-240V
POWER CONSUMPTION	5.75 Watts (max)
ENVIRONMENTAL	
OPERATING TEMPERATURE	0~40°C [32~104°F]
STORAGE TEMPERATURE	-20~60°C [-4~140°F]
RELATIVE HUMIDITY	20~90% RH [no condensation]