

## Triple 5-IN RACK DISPLAY MONITOR (3G-SDI, HDMI, COMPOSITE)

# M-1051H

**SWIT®**



### Introduction:

The M-1051H is an affordable 3-in-1 monitor that offers wide connectivity options and all of the essential features required of a broadcast monitor. This monitor is perfect for studio and field packs.

### Package includes:



2-pin AC-DC adapter



LCD Protector

**SWIT Electronics Co., Ltd.**

Website: [www.swit.cc](http://www.swit.cc)  
Email: [contact@swit.cc](mailto:contact@swit.cc)  
Tel: +86 25 85805753  
Fax: +86 25 85805296

**Distributed by:**

### Features:

- ◆ Three 5-inch LCD Panels (800×480 pixels)
- ◆ 16:9 / 4:3 adjustable
- ◆ 3G/HD/SD-SDI, HDMI, Composite video, Stereo audio inputs
- ◆ 3-color TALLY light (for each display)
- ◆ Underscan / Overscan switch
- ◆ Two-level zoom-in
- ◆ Video flip
- ◆ Customer editable video TITLE
- ◆ SDI embedded audio output
- ◆ Fits standard 19-inch EIA rack (3RU), 30° tiltable
- ◆ Easy menu-driven setup

### Specifications:

#### LCD Performance

Size	5.0 inches×3
Resolution	800×RGB×480
Aspect ratio	16:9/4:3
Color system	NTSC/PAL
Brightness	350cd/m2
Contrast	500:1
Color	16.77 million colors
Viewing angle	H/V:140/120

#### Input and Output (each display)

Input	1 BNC	1 3G/HD/SD-SDI in
	1 BNC	1 Composite in
	1 HDMI	1 HDMI in
	2 RCA	Stereo audio (L, R) in
Output	1 BNC	1 3G/HD/SD-SDI loop through out
	1 BNC	1 Composite loop through out
	1 HDMI	1 HDMI loop through out

#### Video Format

SDI	SMPTE-425M	1080P (60 / 59.94 / 50)
	SMPTE-274M	1080i (60 / 59.94 / 50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
HDMI	480i / 576i / 480P / 576P	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
Composite	PAL/NTSC	

#### General

Working voltage	DC 6.5V-17V
Power consumption	≤24W
Working temperature	0 C ~ +40 C
Working humidity	10% ~ 90%
Storage temperature	-15 C ~ +60 C
Storage humidity	10% ~ 90%
Dimensions	480×130×42mm, Standard 19" rack, 3U height
Net weight	2100g