

SWIT M-1073H Dual 7-inch FHD Rack LCD Monitor

LCD Performance		
Size		7 inches
Display area		151.2x94.5mm
Resolution		1920x1200
Aspect ratio		16:9 (4:3 adjustable)
Brightness		400cd/m2
Contrast		1000:1
Color		16.77 million colors
Viewing angle		Horizontal: 160°; Vertical: 160°
Input(Each LCD)		
BNC x2		2K/3G/HD/SD-SDI input
HDMI x1		HDMI 2.0 input
USB x1		Firmware upgrade
RS485 x1		GPI (Tally) input
Output(Each LCD)		
BNC x1		2K/3G/HD/SD-SDI loop output
HDMI x1		HDMI 2.0 loop output
3.5mm x1		SDI, HDMI embedded audio output
Video Format		
SDI	SMPTE 2048-2	2048x1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98) 2048x1080i (60 / 59.94 / 50)
	SMPTE-425M	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080i (60 / 59.94 / 50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
HDMI		4096x2160p (60 / 50 / 30 / 25 / 24)
		3840x2160p (60 / 50 / 30 / 25 / 24)
		480i/ 576i / 480p / 576p
		1080i (60 / 59.94 / 50)
		720p (60 / 59.94 / 50) 1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)
General		
Working voltage		DC / battery 6.5V-36V
Power consumption		18-26W
Working temperature		-10°C■+50°C
Working humidity		10%■90%
Storage temperature		-15°C■+60°C
Storage humidity		10%■90%
Dimensions		485x130x82mm
Net weight (main body)		2.4kg