

**Bolide SVR9516H 16-Channel Hybrid 5.0MP DVR with Control over Coax**

<b>DISPLAY</b>	
Resolution	Analog: 5MP (20fps) 4MP/3MP (30fps) 1080P/720P/960H IP: 4MP/3MP/1080P/720P
Feature	1/4/6/8/9/10/13/14/16/17/19/22/2 5/S.E.Q
<b>RECORD</b>	
Resolution	Analog:5MP/4MP/3MP/1080P/720P/960 IP: 3MP/1080P/720P/960H
Speed	Analog: 5MP: 11fps ( each ch.) 4MP: 15fps ( each ch. ) 3MP: 12fps ( each ch. ) 1080P: PAL: 15fps ( each ch. ) NTSC: 30fps ( each ch. ) 720P: PAL: 25fps ( each ch. ) NTSC: 25fps ( each ch. ) 960H: PAL: 25fps ( each ch. ) NTSC: 30fps ( each ch. ) IP: PAL:25fps(each ch) NTSC: 30fps(each ch)
Video Compression	H.264
Video System	NTSC/PAL
Operating System	Linux (embedded)
Analog Video In/Out	16CH input / VGA & HDMI output
IP Video Input	Up to 8 CH
Composite Video Input	Up to 16 CH
Audio Input / Output	4CH inputs / 1 CH output (RCA)
IP-Rec Bandwidth	64Mbps~ 96Mbps
Max. Output Bandwidth	128Mbps
Max. Decode Perf.	5MP: 176fps 4MP: 240fps 1080P: 480fps
Recording Mode	Continuous/Manual/Motion detect
Synch. Playback	16 CH
Network Type	TCP/IP, P2P, 1 SATA HDD, up to 8T
HDD Interface	2 x SATA, Up to 8TB per bay
USB	2 x USB (for mouse and backup)
Sensor & Alarm I/O	NO
PTZ Control	Yes (RS485) Control over Coax
Mobile Surveillance	Supports mobile phones: iPhone/Android
VGA/HDMI	1280*1024 1440*900 1280*720 1920*1080 1680*10501600*1200 1920*1200 2560*1440 3840*2160
Power Supply	DC12V/2A
Dimensions	300 x 227 x 53mm
Working Temperature/td>	-10°C~+55°C

