SWIT S-4904P SDI/HDMI Wireless Extender (Transmitter/Receiver) System up to 1000m/3280ft

Model S-4904P	Transmitter	Receiver	
lagut	3G/HD/SD-SDIx1	/	
Input	HDMIx1	7	
Output	/	3G/HD/SD-SDIx1	
Format	1080P (60 / 59.94 / 50)		
	1080i (60 / 59.94 / 50)		
	1080p (30 / 29.97 / 25 / 24 / 23.98)		
	1080psf (30 / 29.97 / 25 / 24 / 23.98)	The same as transmitter inputs	
	720p (60 / 59.94 / 50)		
	480i (59.94)		
	576i (50)		
Wireless frequency	5150 ■ 5850MHz	5150 ■ 5850MHz	
Radio modules	OFDM 16QAM	OFDM 16QAM	
Max Transmission distance	Approx 1000m (Line of sight)	Approx 1000m (Line of sight)	
Latency	≤1 millisecond	≤1 millisecond	
Power consumption	≤6.5W	≤7W	
Radio power	Max 21dBm (63mW)	/	
Receiving antenna gain	/	14dBi±0.5	
Input voltage	DC / Battery:6.5~17V	DC / Battery:DC 7∎36V	
Working environment	Temperature: 0°C -+40°C	Temperature: 0°C -+40°C	
Dimension	93x185x63 (mm)	305x305x58.5 (mm)	
Net weight(with antenna)	572g (with antenna)	2380g(with VESA bracket)	