

SWIT S-4904T/R SDI/HDMI Wireless Extender (Transmitter/Receiver) System/Gold or V-Mount up to 2200ft

| Model | | Transmitter S-4904T | Receiver S-4904R |
|---------------------------|-------------------------------|--------------------------------------------------------|------------------|
| Input | | 3G/HD/SD-SDIx1 | / |
| | | HDMIx1 | |
| Output | | / | 3G/HD/SD-SDIx1 |
| | | | HDMIx1 |
| SDI Format | SMPTE-425M | 1080P (60 / 59.94 / 50) | |
| | SMPTE-274M | 1080i (60 / 59.94 / 50) | |
| | | 1080p (30 / 29.97 / 25 / 24 / 23.98) | |
| | SMPTE-RP211 | 1080psf (30 / 29.97 / 25 / 24 / 23.98) | |
| | SMPTE-296M | 720p (60 / 59.94 / 50) | |
| | SMPTE-125M | 480i (59.94) | |
| | ITU-R BT.656 | 576i (50) | |
| HDMI format | | 1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98) | |
| | | 1080i (60 / 59.94 / 50) | |
| | | 720p (60 / 59.94 / 50) | |
| | | 480i / 576i | |
| Wireless frequency | 5.1 ~ 5.9GHz | | |
| Radio modules | OFDM 16QAM | | |
| Max Transmission distance | Approx 2200ft (Line of sight) | | |
| Latency | ≤1 millisecond | | |
| Power consumption | ≤6.5W | ≤6.5W | |
| Radio power | Max 21dBm (63mW) | / | |
| Input voltage | DC / Battery:6.5~17V | DC / Battery:6.5~17V | |
| Working environment | Temperature: 0°C ~+40°C | | |
| Dimension | 93x185x63 (mm) | 130x188x47 (mm) | |
| Net weight(with antenna) | 572g | 797g | |