

Kramer FC-101NET 2-Channel Dante Decoder and PoE Acceptor

OUTPUTS

- 1 Balanced Stereo Audio/2 Mono Audio: On a 5-pin terminal block

PORTS

- 1 Dante: On an RJ-45 connector

CONTROL

- Dante IP control matrix and Kramer Protocol 3000

POWER

- Source: 48V DC (PoE)
- Consumption: 100mA

ENCLOSURE

- Size: Pico TOOL
- Type: Aluminum
- Cooling: Convection ventilaion

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

STANDARDS COMPLIANCE

- Safety: CE

ENVIRONMENTAL

- RoHs, WEEE

ACCESSORIES

- Included: Bracket set, double-sided adhesive dual lock tape
- Optional: RK-4PT rack adapter

PRODUCT DIMENSION

- 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H

PRODUCT WEIGHT

- 0.1kg (0.2lbs) approx.

SHIPPING DIMENSION

- 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

HIPPING WEIGHT

- 0.2kg (0.5lbs) approx.