

SWIT S-4914T/R SDI/HDMI Wireless Extender (Transmitter/Receiver) System/Gold or V-Mount up to 2200ft

Model		Transmitter S-4914T	Receiver S-4914R
Input		3G/HD/SD-SDIx1	/
		HDMIx1	
Output		/	3G/HD/SD-SDIx1
			HDMIx1
SDI Format	SMPTE-425M	1080P (60 / 59.94 / 50)	
	SMPTE-274M	1080i (60 / 59.94 / 50)	
		1080p (30 / 29.97 / 25 / 24 / 23.98)	
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)	
	SMPTE-296M	720p (60 / 59.94 / 50)	
	SMPTE-125M	480i (59.94)	
	ITU-R BT.656	576i (50)	
HDMI format		1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
		1080i (60 / 59.94 / 50)	
		720p (60 / 59.94 / 50)	
		480i / 576i	
Wireless frequency	5.1 ~ 5.9GHz		
Radio modules	OFDM 16QAM		
Max Transmission distance	Approx 2200ft (Line of sight)		
Latency	≤1 millisecond		
Power consumption	≤6.5W	≤6.5W	
Radio power	Max 21dBm (63mW)	/	
Input voltage	DC / Battery:6.5~17V	DC / Battery:6.5~17V	
Working environment	Temperature: 0°C ~+40°C		
Dimension	71x120x37 (mm)	130x188x47 (mm)	
Net weight(with antenna)	300g	797g	