

FEATURES

- Coax Control
- IR LEDs 4 pcs.
- IR Range: Up to 328 ft.
- IR Mode: Auto, All On, All Off
- 360° Continuous rotation
- Maximum 255 preset positions
- 4 patrol groups
- Weather-Rating IP66

SPECIFICATIONS

Image Sensor	1 / 3" CMOS
Resolution	1920 (H) x 1080 (V)
Video Format	PAL/NTSC
Min. Illumination	Color: 0.05 Lux @F1.6 B/W: 0.01 Lux @F1.6
IR Distance	328 ft.
Remote Controlling	RS485 and Control over Coax
Video Output	AHD (1Vp-p 75 ohm)
Output Connection	BNC
S/N Ratio	52dB
White Balance	Auto
Day & Night	IR-CUT
ICR	Manual / Auto
DNR	Auto / Off / Low / Middle / High
HLC	Off / On
Max Gain	Auto
IRIS	Auto
FLIP	Vertical, Horizontal, Vertical-Horizontal OFF Selectable



Pan & Tilt

Manual Speed	Pan (0.1° ~ 200°/s) Tilt (0.1° ~ 180°/s)
Rotation	Pan continuously 360°, tilt 0~90° with auto-flip
Preset	128 preset, title can be edited
Auto-Flip	Tilt Down 90°, with auto-flip 180°
Scan	355° programmable, 4 scan
Pattern	4 patterns: each record time is < 180s
Tour	4 tours: speed and & park time can be set
Idle Run	Tour / preset / pattern / scan can be set
Power Up Run	Tour / preset / pattern / scan can be set

LENS

Focal Length	F= (4.6mm – 165.6mm)
Optical Zoom	36X Optical Zoom
Auto Focus	Auto / Semi-automatic / Manual
Angle	Approx.: 55.2° (Wide) to 3.2° (Tele)
Zoom Speed	Approx.: 3.0s (Optical Wide-Tele)

GENERAL

Power Supply	24VAC 2A
Power Consumption	9W / 35W (IR LED ON)
Operating Temp.	-10°C ~ 50°C
Protection Level	TVS Lightening protection, Surge protection and voltage transient protection
Weather-Rating	IP66
Material	Metal-Cast Aluminum
Size	185.0 mm X 374 mm
Weight	2.7 kg