

Bolide BE-8216E/POE 16 Port Security Grade Managed PoE Switch/100-240VAC

Power	
Power Supply	Mains on load
Voltage Range	AC 100-240V
Consumption	320W
Network Connector	
Ethernet Port	1-16, ports: 10/100Mbps Ethernet Port Adaptive control UPLINK Ethernet port: 10/100/1000Mbps Ethernet Port SFP: SFP optical fiber module, 1000Mbps
Transmission Distance	1-16ports: Recommended 120m Max. 150m; Uplink1000Mbps ethernet port: Ma.x150m SFP: depends on the optical module performance
PoE Protocol	IEEE802. 3af. IEEE802. 3at
PoE Power Supply	End-span
PoE Power Consumption	Each Port \leq 30W Total \leq 250W
Network Switch	
Network Standard	IEEE802.10BASE-T, IEEE802. 3u 100BASE-TX, IEEE802.3ab 1000BASE-T,IEEE802. 3Z 1000BASE-SX/LX
Switch Capacity	16G
Management	
Management	Management L2
Protection	
ESD	Level 3, Per IEC61000-4-2
Communication Port Lightning Protection	Level 3, Per IEC61000-4-5
Environmental	
Working Temperature	0°C - 55°C / 32F - 131F
Storage Temperature	-40°C - 85°C / -40F - 185F
Humidity (Non-condensing)	0-95%
Mechanical	
Dimension (LxWxH)	442mmx315mmx44mm
Material	Sheet Metal
Color	Black