

BN7009H H.265

4MP High Definition Wide Angle IR Dome Camera





HIGHLIGHTS

- 2.8 mm Wide Angle Lens
- H.265 Compression
- Built-In POE
- IR Distance up to 75 ft.
- IP66 Weather-proof Housing
- BNC Output
- Two-Way (Audio In/Out)
- Edge Recording

The new iPac NX series features up to 4 Mega Pixels of stunning Ultra HD resolution combined with the Next Generation of compression standards - High Efficiency Video Coding (HEVC / H.265)- which allows for bitrates nearly half those of other cameras utilizing older H.264 compression technology. The iPac NX series offers double the storage and half of the bandwidth requirements without sacrificing resolution or frame rate.

MECHANICAL SPEC	ts without sacrificing resolution or frame rate.
Image Sensor	1/3" Progressive Scan CMOS
Minimum Illumination	0.01 Lux @(F1.2,AGC ON), 0.028 Lux
	@ (F1.2,AGC ON), 0 Lux with IR
Shutter Speed	1/5 s – 1/20,000 s
Lens Type	2.8 mm
Lens Mount	M12
Day and Night	IR Cut Filter with Auto Switch
Dynamic Range	Wide Dynamic Range
Digital Noise	2D / 3D DNR
Reduction	
COMPRESSION	
Video Compression	H.265 / H.264 / MJPEG
Image Resolution	4MP (2592 x 1520)
	3MP (2048 x 1536)
	1296P (2304 x 1296)
	1080P (1920 x 1080)
Video Bit Rate	256K-8M
IMAGE	
Frame Rate	4MP (2592 X 1520) @ 20fps
	3MP (2048 x 1536) @ 30fps
	2MP 1296P (2304 x 1296) @ 30fps
	1080P (1920 x 1080) @ 30fps
	720P (1280 x 720) @30 fps - 960H (1280 x 960)
	Substream @ 30 fps
	D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240)
	@30 fps
	Mobilestream @ 10 fps
	QVGA (320 X 240) - @1-30 fps
Image Settings	Rotate Mode, Saturation, Brightness, Contrast,
	Sharpness, and adjustable browser
Day and Night Switch	Auto / Schedule / Triggered by Alarm In
INTERFACE	Nato / Schedule / Higgered by Maini III
System Compatibility	ONVIF 2.4, RSSP
Interface	1 RJ45 10M / 100M Ethernet Interface
IR Distance	Up to 75 ft.
POE	Built-In POE
Edge Recording	Micro SD slot
Security	Flash-Prevention, Dual Stream, Heartbeat, Mirror,
Security	Password Protection, Privacy Mask, IP Address Filtering,
	SRTP
ELECTRICAL	
Power Supply	12 VDC ± 10%, POE (802.3af)
Power Consumption	Max. 5 W (Max. 7W with IR cut filter on)
Operating Temp.	-22 °F - 140 °F Humidity 95% or less (non-condensing)
PHYSICAL	22 1 170 1 Humbury 7370 OF 1633 (HOTE-CORDERSHIP)
Net Weight	1 lb.
Weather-Rating	I IP66 Rated and IK10
weather-Rattitu	I IPOO KAIEU AHU IK IU

468 S San Dimas Ave, CA 91773 ISO 9001:2008 Certified Company

www.bolideco.com

sales@bolideco.com T (909) 305-8889 F(909) 305-0999