

5MP High Definition Fixed Lens IR Bullet Camera





HIGHLIGHTS

- 5.0MP Resolution
- Flux IR Up to 75ft
- 1/3" Progressive Scan CMOS
- Compression H.265 / H.264
- Built-In POE
- 3.6 mm Lens

The new iPac NX series features up to 5 Mega Pixels of stunning Ultra HD resolution combined with the Next Generation of compression standards - High Efficiency Video Coding (HEVC / H.265)- which allows for bitrates nearly half those of other cameras utilizing older H.264 compression technology. The iPac NX series offers double the storage and half of the bandwidth requirements without sacrificing resolution or frame rate.

| MECHANICAL SPECIFICATIONS | |
|---|--|
| Image Sensor | 1/3" Progressive Scan CMOS |
| Minimum Illumination | 0.01 Lux @(F1.2,AGC ON), 0.028 Lux |
| | @ (F1.2,AGC ON), 0 Lux with IR |
| Shutter Speed | 1/5 s - 1/20,000 s |
| Lens Type | 3.6 mm |
| Lens Mount | M12 |
| Day and Night | IR Cut Filter with Auto Switch |
| Dynamic Range | Wide Dynamic Range |
| Digital Noise | 2D / 3D DNR |
| Reduction | |
| COMPRESSION | |
| Video Compression | H.265 / H.264 / MJPEG |
| Image Resolution | Up to 5MP (2560 X 1960) |
| Video Bit Rate | 256K-8M |
| IMAGE | |
| Frame Rate | 5MP (2560 X 1960) @ 11fps |
| | 4MP (2592 X 1520) @ 20fps |
| | 3MP (2048 x 1536) @ 30fps |
| | 2MP 1296P (2304 x 1296) @ 30fps |
| | 1080P (1920 x 1080) @ 30fps |
| | 720P (1280 x 720) @30 fps - 960H (1280 x 960) |
| | Substream @ 30 fps |
| | D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) |
| | @30 fps |
| | Mobilestream @ 10 fps |
| 1 0 11 | QVGA (320 X 240) - @1-30 fps |
| Image Settings | Rotate Mode, Saturation, Brightness, Contrast, |
| Day and Night Curitah | Sharpness, and adjustable browser Auto / Schedule / Triggered by Alarm In |
| Day and Night Switch Auto / Schedule / Triggered by Alarm In INTERFACE | |
| | CANVIE O A DOOD |
| System Compatibility | ONVIF 2.4, RSSP |
| Interface | 1 RJ45 10M / 100M Ethernet Interface |
| IR Distance POE | Flux IR Up to 75 ft. Built-in POE |
| | |
| Security | Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering |
| ELECTRICAL | rassword Frotection, Frivacy Mask, IP Address Filtering |
| | 10 V/DC - 100/ DOF (000 2-0 |
| Power Supply | 12 VDC ± 10%, POE (802.3af) |
| Power Consumption | Max. 5 W (Max. 7W with IR cut filter on) |
| Operating Temp. | -22 °F - 140 °F Humidity 95% or less (non-condensing) |
| PHYSICAL | I |
| Dimensions | 5.7" x 2.7" x 2.8" |
| Net Weight | .78 lbs. |
| Weather-Rating | IP66 Rated |