

4K Motorized Varifocal Lens IR Bullet Camera


iPac4K




HIGHLIGHTS

- 4K Resolution
- H.265 Compression
- Built-In POE
- IR Distance up to 147 ft.
- 3.3 12mm Motorized Lens
- SD Card slot
- 2 Way Audio
- Alarm In / Out

DIMENSIONS





Bolide Technology Group

468 S San Dimas Ave, CA 91773 ISO 9001:2008 Certified Company The new iPac 4K is a true next generation of video surveillance cameras. 8MP resolution displays crisp 4K resolution with more accurate line, colors, and improved capabilities to identify people and objects in a video surveillance application. This solution is suitable for coverage of large areas and events where extensive digital zoom is required. Every iPac 4K camera also packs features that simplify installations and add utility such as audio recording and alarm relays.

Minimum Illumination 0.01Lux @(F1.2,AGC ON); B/W 0 Lux with IR	MECHANICAL SPECIFICATIONS	
Shutter Speed	Image Sensor	1/2.5" Progressive CMOS
Lens	Minimum Illumination	0.01Lux @(F1.2,AGC ON); B/W 0 Lux with IR
F No.	Shutter Speed	1/5 s - 1/20,000 s
F No.	Lens	3.3 – 12mm Motorized Lens; FOV 114 – 36°
Digital Digital	F No.	
Digital Noise	Day and Night	IR Cut Filter with Auto Switch
Reduction	WDR	Digital
COMPRESSION Video Compression H.265 / H.264 Image Resolution Up to 8MP (3840 x 2160) Video Bit Rate 8Kbps ~ 16Mbps IMAGE Frame Rate 8MP (3840 x 2160) 4MP (2592 x 1520) 3MP (2048 x 1536) 2MP 1296P (2304 x 1296 1080P (1920 x 1080) 720P (1280 x 720) - 960H (1280 x 960) Substream D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) Mobilestream QVGA (320 X 240) Image Settings Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface 1 RJ45 10M / 100M Ethernet Interface IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp. -40 °F - 140 °F Humidity 95% or less (non-condensing) <td< td=""><td>Digital Noise</td><td>2D / 3D DNR</td></td<>	Digital Noise	2D / 3D DNR
Video Compression H.265 / H.264 Image Resolution Up to 8MP (3840 x 2160) Video Bit Rate 8Kbps ~ 16Mbps IMAGE Frame Rate 8MP (3840 x 2160) 4MP (2592 x 1520) 3MP (2048 x 1536) 2MP 1296P (2304 x 1296 1080P (1920 x 1080) 720P (1280 x 720) - 960H (1280 x 960) Substream D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) Mobilestream QVGA (320 X 240) Image Settings Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface 1 RJ45 10M / 100M Ethernet Interface IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp. -40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions <td>Reduction</td> <td></td>	Reduction	
Image Resolution	COMPRESSION	
Video Bit Rate 8Kbps ~ 16Mbps	Video Compression	H.265 / H.264
IMAGE	Image Resolution	Up to 8MP (3840 X 2160)
Route	Video Bit Rate	
Route	IMAGE	
AMP (2592 x 1520) 3MP (2048 x 1536) 2MP 1296P (2304 x 1296 1080P (1920 x 1080) 720P (1280 x 720) - 960H (1280 x 960) Substream		8MP (3840 x 2160)
3MP (2048 x 1536) 2MP 1296P (2304 x 1296 1080P (1920 x 1080) 720P (1280 x 720) - 960H (1280 x 960) Substream D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) Mobilestream QVGA (320 X 240) Mobilestream QVGA (320 X 240) Image Settings Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface 1 RJ45 10M / 100M Ethernet Interface IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp. -40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
2MP 1296P (2304 x 1296 1080P (1920 x 1080) 720P (1280 x 720) - 960H (1280 x 960) Substream D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) Mobilestream QVGA (320 X 240) Image Settings Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface IR Distance IR Distance QUGA (320 X 240) Interface IR Distance IR Distance IR Distance IR Distance POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
1080P (1920 x 1080) 720P (1280 x 720) - 960H (1280 x 960) Substream D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) Mobilestream QVGA (320 X 240) Image Settings Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface IR Distance IR Distance POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
720P (1280 x 720) - 960H (1280 x 960) Substream D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) Mobilestream QVGA (320 X 240) Image Settings Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface IR Distance IR Distance POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply Power Consumption Operating Temp. 40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
Substream D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) Mobilestream QVGA (320 X 240) Image Settings Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface IR Distance IR Distance POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) Mobilestream QVGA (320 X 240) Image Settings Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface IR Distance IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Operating Temp. 40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
Mobilestream QVGA (320 X 240)		
Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser		
Image Settings Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface 1 R J45 10M / 100M Ethernet Interface IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
Sharpness, and adjustable browser Day & Night IR Cut Filter with Auto Switch INTERFACE System Compatibility ONVIF 2.6 Interface 1 RJ45 10M / 100M Ethernet Interface IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.	Image Settings	Rotate Mode, Saturation, Brightness, Contrast,
INTERFACE System Compatibility ONVIF 2.6 Interface 1 RJ45 10M / 100M Ethernet Interface IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
INTERFACE System Compatibility ONVIF 2.6 Interface 1 R J45 10M / 100M Ethernet Interface IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.	Day & Night	IR Cut Filter with Auto Switch
Interface 1 R J45 10M / 100M Ethernet Interface IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
IR Distance 40pcs LED Up to 148 feet POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
POE Built-In POE Security Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.	Interface	1 RJ45 10M / 100M Ethernet Interface
Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.	IR Distance	
Password Protection, Privacy Mask, IP Address Filtering ELECTRICAL Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.	POE	
Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.	Security	
Power Supply 12 VDC ± 10%, POE (802.3af) Power Consumption Max. 9 W Operating Temp. -40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		Password Protection, Privacy Mask, IP Address Filtering
Power Consumption Max. 9 W Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
Operating Temp40 °F - 140 °F Humidity 95% or less (non-condensing) PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.		
PHYSICAL Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.	Power Consumption	
PHYSICALDimensions9.3" x 2.9" x 4"Net Weight1.94 lbs.	Operating Temp.	-40 °F - 140 °F Humidity 95% or less (non-condensing)
Dimensions 9.3" x 2.9" x 4" Net Weight 1.94 lbs.	PHYSICAL	
Net Weight 1.94 lbs.		9.3" x 2.9" x 4"
	Weather-Rating	IP66 Rated