

Altinex TP115-401-1 HOMERUN HDMI over IP Extender (Transmitter/Receiver) Kit

Features/Description TP115-401	
Input Connectors	
HDMI	HDMI F, Type A (1)
DC Power	2.5 mm center pin (1)
Output Connectors	
Local HDMI	HDMI F, Type A (1)
IP	RJ45 F, Shielded (1)
Audio (Analog)	3.5 mm stereo (1)
Control	
IRTX	3.5 mm F (1)
RS232	3.5 mm F (1)
Factory Reset	Push Button
Compatibility	
Signal types	HDMI, audio
Video Signal resolutions	480p/720p/1080i/1080p
Streaming Bit Rate	15 Mbps
IR Frequency	Support 38 kHz
RS232 Baud rate	Default 2400 bps
Accessories Included	
Power supply	+12V, 2A US, EU, AU, UK plugable blades
IRTX	n/a
Mounting hardware	2 brackets, 8 screws
Mechanical	TP 115-401
Material	Aluminum
Color	Black
Height	1 in (25 mm)
Width	5.3 in (135 mm)
Depth	3.1 in (79 mm)
Weight	0.35 lb. (0.16 kg)
T° Operating	10°C-45°C
Humidity	90% non-condensing
MTBF (calc.)	38,000 hrs.
Electrical	TP115-401
Video Input Signals	
Video	HDMI Standard
Video Output Signals	
Digital Video + Audio	HDMI over IP
Analog Audio	Line Level
Power	
12V	0.35A
Total Power	4.2W
Features/Description TP115-402	
Input Connectors	
IP	RJ45 F, Shielded (1)
DC Power	2.5 mm center pin (1)
Output Connectors	
HDMI	HDMI F, Type A (1)
Audio (Analog)	3.5 mm stereo (1)

Balanced Analog Audio	5-pin terminal block (1)
Control	
IRRX	3.5 mm F (1)
RS232	3.5 mm F (1)
Factory Reset	Push Button
Compatibility	
Signal types	HDMI, audio
Video Signal resolutions	480p/720p/1080i/1080p
Streaming Bit Rate	15 Mbps
IR Frequency	Support 38 k - 56 kHz
RS232 Baud rate	Default 2400 bps
Accessories Included	
Power supply	+12V, 2A US, EU, AU, UK plugable blades
IRRX	
Connector	5-pin plug for RS-232 cable termination (1)
Mounting hardware	2 brackets, 8 screws
Electrical	TP115-402
Video Input Signals	
Digital Video + Audio	HDMI over IP
Video Output Signals	
Video	HDMI Standard
Audio Output Signals	
Analog Audio	Line Level
Balanced Analog Audio	Line Level
Power	
12V	0.35A
Total Power	4.2W
Mechanical	TP 115-402
Material	Aluminum
Color	Black
Height	1 in (25 mm)
Width	5.3 in (135 mm)
Depth	3.1 in (79 mm)
Weight	0.35 lb. (0.16 kg)
T° Operating	10°C-45°C
Humidity	90% non-condensing
MTBF (calc.)	38.000 hrs.