

LTS CMIP1043W-MZ Platinum Matrix Varifocal Turret Network IP Camera 4MP

| | |
|--------------------------|-----------------|
| Camera Series | Platinum Series |
| Camera Resolution | 4MP |
| Camera Technology | IP / Network |
| Camera Housing | Turret |
| Featured Product | No |

Specifications

| | |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Camera | |
| Image Sensor | 1/3" Progressive Scan CMOS |
| Min. Illumination | 0.01Lux @ (F1.2, AGC ON), 0 Lux with IR |
| Shutter Speed | 1/3 s to 1/10,000 s |
| Lens | 2.8 mm to 12 mm @F1.4, horizontal field of view: 98° to 30° |
| Lens Mount | Φ 14 |
| Day & Night | IR cut filter with auto switch |
| DNR | 3D DNR |
| Wide Dynamic Range | 120dB |
| Angle Adjustment | Pan: 0° to 360°; Tilt: 0°to 65°; Rotation:0° to 360° |
| Compression Standard | |
| Video Compression | Main stream: H.264 Zip+ /H.264 Sub stream: H .264/MJPEG |
| H.264 Type | Main Profile / High Profile |
| Video Bit Rate | 32 Kbps ~ 16 Mbps |
| Image | |
| Max. Resolution | 2688x1520 |
| Main Stream | 60Hz: 20 fps (2688 × 1520), 20fps (2304 × 1296), 30 fps (1920 × 1080, 1280 ×720) 50Hz: 20 fps (2688 × 1520), 20fps (2304 × 1296), 25 fps (1920 × 1080, 1280 ×720) |
| Sub Stream | 60Hz: 30fps (640 × 360, 352 × 240) / 50Hz: 25fps (640 × 360, 352 × 288) |
| Image Setting | Support rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser or client software |
| BLC | Support, zone configurable |
| Others | Mirror, BLC (area configurable), region of interest (support 1 fixed region) |
| Network | |
| Network Storage | NAS (NFS,SMB/CIFS) |
| Alarm Trigger | Motion detection |
| Protocols | TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour |
| General | One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter |
| Standard | ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI |
| Interface | |
| Communication Interface | 1 RJ45 10M/100M Ethernet port |
| Reset | Yes |
| General | |
| Working Temperature /Humidity | -22 °F ~ 140 °F (-30 °C ~ 60 °C) Humidity 95% or less (non-condensing) |
| Power Supply | DC12V ± 25%, PoE (802.3af) |
| Power Consumption | Max. 8.5W/wwW (PoE) |
| IR Range | 66ft to 100ft |
| Weather Proof Ratings | IP67 |
| Dimensions | Φ 5.14" × 4.03" (Φ 130.5 × 102.4 mm) |
| Weight | 1.07lb. (485 g) |