ViewSonic VA2259-SMH 22 inch (21.5in VIS) Full HD 1080p SuperClear IPS LED monitor/HDMI and VGA inputs/dual 2W speakers

•	Display:	
	Display Size (in.):	22
	Viewable Area (in.):	21.5
	Panel Type:	IPS
	Resolution:	1920 x 1080
	Static Contrast Ratio:	1,000:1
	Dynamic Contrast Ratio:	50,000,000:1
	Light Source:	LED
	Brightness:	250 cd/m2
	Colors:	16.7M
	Response Time (Typical GTG):	14ms
	Response Time (GTG w/OD):	7ms
	Viewing Angles:	178º horizontal, 178º vertical
	Backlight Life (Hours):	30,000
	Panel Surface:	Anti-glare, hard-coating (3H)
•	Compatibility:	
	PC Resolution (max):	Up to 1920x1080 non-interlaced
	Mac® Resolution (max):	Up to 1920x1080
•	Connector:	
	3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug	(CEE22))
•	Audio:	
	Internal Speakers:	2-watt (x2)
•	Power:	
	Eco Mode (Conserve):	14W
	Eco Mode (optimized):	18W
	Consumption (typical):	22W
	Consumption (max):	27W
	Voltage:	AC 100-240V (universal), 50-60Hz
•	Additional Hardware:	
	Kensington Lock Slot:	1
•	Controls:	
	Physical Controls:	1, 2, Down, Up, Power
	Physical Controls:	1, 2, Down, Up, Power Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color
	Physical Controls: On Screen Display:	
		Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color
•		Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup
•	On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup
•	On Screen Display: Operating Conditions:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
•	On Screen Display: Operating Conditions: Temperature:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C)
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C)
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90%
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90%
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm
	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal: Frequency Horizontal:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz
	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: ViESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green, TMDS
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back): Weight (imperial):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22°
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: ViESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back): Weight (imperial): Net (lbs):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: ViESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back): Weight (imperial): Net (lbs): Net Without Stand (lbs):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: ViESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back): Weight (imperial): Net (lbs): Net Without Stand (lbs): Gross (lbs):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back): Weight (imperial): Net (lbs): Net Without Stand (lbs): Gross (lbs): Weight (metric):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back): Weight (imperial): Net (lbs): Net Without Stand (lbs): Gross (lbs): Weight (metric): Net (kg):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back): Weight (imperial): Net (lbs): Net Without Stand (lbs): Gross (lbs): Weight (metric): Net (kg): Net Without Stand (kg):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5
•	On Screen Display:Operating Conditions:Temperature:Humidity (non-condensing):Mount:VESA Compatible:Video Signal:Frequency Horizontal:Frequency Vertical:Video Input:Analog Sync:Ergonomics:Tilt (Forward/Back):Weight (imperial):Net (lbs):Net Without Stand (lbs):Gross (lbs):Weight (metric):Net (kg):Net Without Stand (kg):Gross (kg):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: ViESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back): Weight (imperial): Net (lbs): Net Without Stand (lbs): Gross (lbs): Weight (metric): Net (kg): Net Without Stand (kg): Gross (kg): Dimensions (imperial) (WxHxD):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5
•	On Screen Display: Operating Conditions: Temperature: Humidity (non-condensing): Mount: VESA Compatible: ViESA Compatible: Video Signal: Frequency Horizontal: Frequency Vertical: Video Input: Analog Sync: Ergonomics: Tilt (Forward/Back): Weight (imperial): Net (lbs): Net Without Stand (lbs): Gross (lbs): Weight (metric): Net (kg): Net Without Stand (kg): Gross (kg): Dimensions (imperial) (WxHxD): Packaging (in.):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5 2.8 2.5 4.3
•	On Screen Display:Operating Conditions:Temperature:Humidity (non-condensing):Mount:VESA Compatible:Video Signal:Frequency Horizontal:Frequency Vertical:Video Input:Analog Sync:Ergonomics:Tilt (Forward/Back):Weight (imperial):Net Without Stand (lbs):Gross (lbs):Weight (metric):Net (kg):Net Without Stand (kg):Gross (kg):Dimensions (imperial) (WxHxD):Packaging (in.):Physical (in.):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5 2.8 2.5 4.3 22.1 x 17.4 x 6.1 19.7 x 14.8 x 7.9
•	On Screen Display:Operating Conditions:Temperature:Humidity (non-condensing):Mount:VESA Compatible:Video Signal:Frequency Horizontal:Frequency Vertical:Video Input:Analog Sync:Ergonomics:Tilt (Forward/Back):Weight (imperial):Net (lbs):Gross (lbs):Weight (metric):Net (kg):Net Without Stand (kg):Gross (kg):Dimensions (imperial) (WxHxD):Packaging (in.):Physical (in.):Physical Without Stand (in.):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5 2.8 2.5 4.3
•	On Screen Display:Operating Conditions:Temperature:Humidity (non-condensing):Mount:VESA Compatible:Video Signal:Frequency Horizontal:Frequency Vertical:Video Input:Analog Sync:Ergonomics:Tilt (Forward/Back):Weight (imperial):Net (lbs):Gross (lbs):Weight (metric):Net (kg):Net Without Stand (kg):Gross (kg):Dimensions (imperial) (WxHxD):Packaging (in.):Physical (in.):Physical (in.):Dimensions (metric) (WxHxD):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24–82kHz 50–75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5 2.8 2.5 4.3 22.1 x 17.4 x 6.1 19.7 x 14.8 x 7.9 19.7 x 11.9 x 1.8
•	On Screen Display:Operating Conditions:Temperature:Humidity (non-condensing):Mount:VESA Compatible:Video Signal:Frequency Horizontal:Frequency Vertical:Video Input:Analog Sync:Ergonomics:Tilt (Forward/Back):Weight (imperial):Net (lbs):Gross (lbs):Weight (metric):Net (kg):Net Without Stand (kg):Gross (kg):Dimensions (imperial) (WxHxD):Packaging (in.):Physical (in.):Physical Without Stand (in.):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green, TMDS 5° / 22° 6.3 5.5 9.5 2.8 2.5 4.3 22.1 x 17.4 x 6.1 19.7 x 14.8 x 7.9

Physical (mm): Physical Without Stand (mm):

General:

Regulations: CE. REACH, WEEE, cULus, FCC-B, ICES003, ENERGY STAR 7.0, EPEAT Silver, Mexico CoC, Mexico Energy PACKAGE CONTENTS: VA2259-smh monitor, Power cable, Audio cable, VGA cable, Quick Start Guide, ViewSonic Wizard CD Recycle/Disposal: Please dispose of in accordance with local, state or federal laws. Warranty: Three-year limited warranty on parts, labor and backlight UPC: 766907836530