

Aten UH3234 USB-C Multiport Dock with Power Pass-Through

Computer Connections	1
Connectors	
Computer	1 x USB-C Male
Device	1 x USB 3.1 Gen1 Type A Female with BC1.2* 2 x USB 3.1 Gen1 Type A Female* *The total output of 3 x USB 3.1 Gen1 Type A Female is 10W (5V/2A).
Video Output	1 x DisplayPort Female 1 x HDMI Female 1 x VGA Female
LAN Ports	1 x Gigabit Ethernet Female
Audio	1 x 3.5mm stereo 4-pole microphone and headphone jack
Power	1 x USB-C Female Power Delivery Pass-Through up to 60W* *Supported power profiles include 20V/3A, 12V/3A, 9V/3A and 5V/3A power specification.
Performance	
Flash Memory	1 x SD/SDHC/SDXC card slot* 1 x Micro SD/SDHC/SDXC (up to 128 GB) card slot* *SD and Micro SD Card cannot be used at the same time; functionality accords to the order of insertion.
Video Resolution	Single View :* DisplayPort - 3840 x 2160@30 HDMI - 3840 x 2160@30 VGA - 1920 x 1200@60 Dual View :** DisplayPort/HDMI - 1920 x 1080@60 DisplayPort/VGA - 1920 x 1080@60 *For video output to work through a USB-C port, it must support DP Alt Mode. ** For Dual-View to work, a computer's graphics card must support MST technology. Mac computers only support a single-view output.
Power Consumption	TBD
Environmental	
Operating Temperature	0°C to 40°C (32°F to 122°F)
Storage Temperature	-10°C to 70°C (-4°F to 158°F)
Humidity	10% to 90% relative humidity, non-condensing
Physical Properties	
Housing	Aluminum
Weight	0.32 kg (0.7 lb)
Dimensions (L x W x H)	28.00 x 7.50 x 1.45 cm (11.02 x 2.95 x 0.57 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.