

WyreStorm MX-0808-PP-POH-CUSTOM 8-Slot HDBaseT Modular Matrix Switcher Chassis

- **Dimensions (WxHxD):** 440mm × 100mm x 340mm /17.3" x 3.9 x 13.4"
- **Weight (Kg):** 6.7Kg / 14.8lb
- **Operating Temperature Range:** 0 to +35°C (32 to +95°F)
- **Operating Humidity Range:** 5 to 90 % RH (no condensation)
- **Video Amplifier Bandwidth:** 6.75Gbps
- **Input Video Signal:** 0.5-1.0 volts p-p
- **Input DDC Signal:** 5 volts p-p (TTL)
- **Maximum Single Link Range:** 1080p 36bit Deep Colour
- **Transmission distance: Min:** 5m/16.4ft - **Max:** 60m/197ft (Cat5e/6), 70m/230ft with (Cat6a/7) using WyreStorm RX-1UTP-IR-70-POH display receiver or AMP-001-010 digital amplifier (Under perfect transmission conditions including straight cable runs with no electrical interference, bends, kinks, patch panels or wall outlets.)
- **Video Format Supported: VESA:** 640x480, 800x600,1024x768, 1280x1024, 1600x1200, 1920x1200 DTV/HDTV: 480i/576i/480p/576p/720p/1080i/1080p
- **Output Video:** HDMI v1.4 with full 3D compatibility with Frame packing/sequential (Blu-ray) and Interlaced Stereoscopic (satellite/cable broadcasts)
- **Audio Format Supported:** HDBaseT: DTS-HD, Dolby True HD, multi-channel 5.1, 7.1, stereo - SPDIF Audio: DTS, AC3, PCM 5.1
- **Power Supply:** 100-240V AC
- **Power Consumption:** 170 Watts (Max.)
- **BTU Rating (British Thermal Unit):** 580.1
- **Rack Space Required:** 2U