

Kramer DT-IN4-F32 4-Channel 4K60 HDMI over Long Reach HDBaseT Input Card

INPUTS

- 4 HDBaseT: On RJ-45 connectors

PORTS

- 4 RS-232 and 4 IR ports: On 10-pin terminal blocks

BANDWIDTH PER CHANNEL

- Video: 3.4Gbps
- Serial data: 115200

TOTAL BANDWIDTH

- Video: 10.2Gbps
- Serial data: 115200

MAXIMUM RANGE

- 40m (130ft) — 4K@60Hz (4:2:0) or 4K@30Hz (4:4:4)
- 70m (230ft) — 1080p 12 bit (deep color)
- Note: When using Kramer HDBaseT cables

3D PASS-THROUGH

- Supported

EXTENDED RS-232

- 300 to 115200 baud rate

STANDARDS COMPLIANCE

- HDCP 1.4, HDMI 1.3a, HDBaseT, HDTV compatible

POWER CONSUMPTION

- 10W

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

REGULATORY

- Safety: CE
- Environmental: RoHs and WEEE

INCLUDED ACCESSORIES

- Screw driver

PRODUCT DIMENSION

- 21.60cm x 19.00cm x 2.00cm (8.50" x 7.48" x 0.79") W, D, H

PRODUCT WEIGHT

- 0.3kg (0.7lbs) approx.

SHIPPING DIMENSION

- 25.00cm x 22.50cm x 5.50cm (9.84" x 8.86" x 2.17") W, D, H

SHIPPING WEIGHT

- 0.5kg (1.2lbs) approx.