

Turbosound TLX43 Compact Dual 2 Way 4 inch Line Array Element for Portable and Fixed Installation Applications

Frequency Response	85 Hz – 20 kHz \pm 3 dB 70 Hz – 20 kHz -10 dB
Nominal Dispersion	120° H x 10° V @ -6 dB points
Power Handling (IEC)	LF: 150 W continuous, 600 W peak HF: 30 W continuous, 120 W peak
Sensitivity	LF: 87 dB (1 W @ 1 m) HF: 99 dB (1 W @ 1 m)
Maximum SPL	LF: 109 dB continuous, 115 dB peak HF: 114 dB continuous, 120 dB peak
Impedance	LF: 16 Ω HF: 16 Ω
Crossover Type	External bi-amp
Components	2 x 4" (102 mm) LF driver 1 x 1" (25.4 mm) HF compression driver
Connectors	2 x Neutrik speakON® NL4
Wiring	Pins 1+ / 1- LF, pins 2+ / 2- HF
Dimensions H x W x D	163 x 512 x 290 mm (6.4 x 20.2 x 11.4")
Net Weight	8.0 kg (17.6 lbs)
Construction	12 mm (½") plywood
Finish	Semi matt black paint
Grille	Powder coated perforated steel
Suspension Hardware	Integral variable curvature
TLX43-FLB fly bar TLX43-RC4 road case	