

Turbosound iP12B 1000W Powered 12 inch Subwoofer with Dual Amplifiers for Satellite Speakers

Frequency response	45 Hz - 150 Hz \pm 3 dB 38 Hz - 200 Hz -10 dB
Nominal dispersion	Half space
Maximum SPL	120 dB
Crossover type	Active
Transducers	1 x 12" (305 mm) LF driver
Limiter	Peak and RMS
Maximum output power*	
Subwoofer	600 W
Satelites	2 x 200 W
Type	Class-D
Protection	Short circuit, open circuit, thermal
Output L / R	2 x Neutrik speakON* NL4, pins 1+ / 1-
Input A / B	2 x combo jack / XLR
Sensitivity	4 dBu, nominal
Input impedance	16 k Ω unbalanced, 33 k Ω balanced
Maximum input level	+22 dBu
Link output	XLR
Mains supply	IEC mains connector with integrated power switch
Factory EQ presets	Positioning, Sound mode, phase
Display	LCD 128 x 32, blue, backlit
Equalisation	Bass, middle and treble
Crossover	High pass L-R 24 dB/oct
Protection	Lock-out function for all settings
Frequency range	2402 MHz ~ 2480 MHz
Channel number	79
Version	Bluetooth 4.0 dual mode
Output	8 dBm
Compatibility	Supports A2DP 1.2 profile
Maximum communication range	30 m (without interference)
Connectivity	Master-slave: stereo pairing link
Power consumption	110 W @ 1/8 max power
Voltage (fuses)	
USA / Canada / Japan	100-120 V~, 50/60 Hz (T 6.3 A H 250 V)
UK / Australia / Europe	220-240 V~, 50/60 Hz (T 3.15 A H 250 V)
Korea / China	220-240 V~, 50/60 Hz (T 3.15 A H 250 V)
Dimensions (H x W x D)	485 x 420 x 500 mm (19.1 x 16.5 x 19.7")
Net weight	22.3 kg (49.2 lbs)
Construction	15 mm (5/8") birch plywood sub
Finish	Semi matt black paint
Grille	Powder coated perforated steel