

Turbosound iP15B 1000W Powered 15 inch Subwoofer with Dual Amplifiers for Satellite Speakers

Frequency response	45 Hz - 150 Hz ±3 Db 38 Hz - 200 Hz -10 dB
Nominal dispersion	Half space
Maximum SPL	120 dB
Crossover type	Active
Transducers	1 x 15" (381 mm) LF driver
Limiter	Peak and RMS
Maximum output power*	
Subwoofer	600 W
Satelites	2 x 200 W
Sensitivity	4 dBu, nominal
Input impedance	16 kO unbalanced, 33 kO balanced
Maximum input level	+22 dBu
Hardware	Rotary push-encoder
Software	iOS interface via Bluetooth
Factory EQ presets	Positioning, Sound mode, phase
Display	LCD 128 x 32, blue, backlit
Equalisation	Bass, middle and treble
Crossover	High pass L-R 24 dB/oct
Protection	Lock-out function for all settings
Frequency range	2402 MHz ~ 2480 MHz
Channel number	79
Version	Bluetooth 4.0 dual mode
Output	8 dBm
Compatibility	Supports A2DP 1.2 profile
Maximum communication range	30 m (without interference)
Connectivity	Master-slave: stereo pairing link
Power consumption	110 W @ 1/8 max power
Voltage (fuses)	
USA / Canada / Japan	100-120 V~, 50/60 Hz (T 6.3 A H 250 V)
UK / Australia / Europe	220-240 V~, 50/60 Hz (T 3.15 A H 250 V)
Korea / China	220-240 V~, 50/60 Hz (T 3.15 A H 250 V)
Dimensions (H x W x D)	570 x 460 x 545 mm (22.4 x 18.1 x 21.5")
Net weight	26.3 kg (58.0 lbs)
Construction	15 mm (5/8") birch plywood sub
Finish	Semi matt black paint
Grille	Powder coated perforated steel