

Smartavi DPX-1P-Plus-S DisplayPort/USB/RS-232/Audio Extender (Transmitter/Receiver) Kit over CAT5/5e/6

VIDEO	
Format	DisplayPort 1.2
Maximum Pixel Clock	275 MHz
Input Interface (TX)	(1) DP female
Output Interface (RX)	(1) DP female
Resolution	Up to 4K (3840×2160 @ 30Hz)
DDC	via AUX
Input Equalization	Automatic
Input Cable Length	Up to 15 ft.
Output Cable Length	Up to 15 ft.
USB	
Signal Type	USB 1.1 and USB 2.0 Compatible
Input Interface (TX)	(1) USB Type B (Female)
Output Interface (RX)	(2) USB Type A (Female)
RS-232	
Input Interface (TX)	DB9 (Female)
Output Interface (RX)	DB9 (Female)
Flow Control	Software up to 115,000 kbps
AUDIO	
Frequency Response	30KHz to 80KHz
Audio Input Interface (TX)	(1) 3.5 mm (Female)
Audio Output Interface (RX)	(1) 3.5 mm (Female)
OTHER	
Power	External 100-240 VAC/5VDC3A @20W
Dimensions	9 in W x 2 in H x 3 in D
Weight	1.45 lb per TX/RX unit
Operating Temp.	0-55 °C (32-131°F)
Storage Temp.	-20-85 °C (-4-185 °F)
Humidity	Up to 95%