

Osprey 95-00135 PCI Analog Composite/S-Video Capture Card for Video Only Workflows (100)

Description: Single channel analog video with 4 selectable inputs

Format:

- PCI 32-bit/5 Volt

Video Input:

- Composite
- S-Video

Video Connector:

- 3 x composite (RCA)
- 1 x S-Video (mini-DIN)

Video Modes:

- NTSC/PAL
- 720 x 480 29.97, 30/i (NTSC)
- 852 x 480, 29.97, 30/i (NTSC Wide Screen)
- 720 x 576 25/i (PAL)
- Wide Screen Signaling (WSS)

Dimensions:

- 4.74" L x 2.20" H (12.04 cm L x 5.59 cm H)
- Low profile

Weight:

- ≈ 68 g

Power Consumption:

- 11.5 W

Operating Temp Range:

- 0° to 40° C

Non-Operating Temp Range:

- -40° to +75° C

Rel Humidity Operating:

- Between 5 % and 80 % (noncondensing)

Rel Humidity Non-Operating:

- 95 % RH (non-condensing); gradient 30% per hour

Operating Altitude Range:

- 0 to 3,048 meters (10,000 feet)

Non-Operating Altitude Range:

- 0 to 15,240 meters (50,000 feet)

Warranty:

- 1 year limited hardware warranty

Compliance:

- CE, FCC, ROHS, WEEE