

Osprey 95-00471 PCIe 4 Channel Analog Video Capture Card/Audio/expansion (460e)

Description:

- Four channel analog

Format:

- PCIe (x 1):
- Slots: xl, x4, x8, or xl6
- PCIe 2.0

Video Input:

- Composite
- Component
- S-Video

Video Connector:

- Composite x4 (BNC x 4)
- (BNC - RCA adapters included)
(Additional BNC x 12 optional)*
Y/C x 4 (BNC x 8) (optional)*
*Requires AV option board

Video Modes:

- NTSC/PAL
- 720 x 480 29.97, 30/i (NTSC)
- 852 x 480, 29.97, 30/i (NTSC Wide Screen)
- 720 x 576 25/i (PAL)
- Wide Screen Signaling (WSS)

Audio Input:

- Unbalanced stereo x4 (RCA x 8)
- Balanced stereo x4 (XLR x 8) (optional)*
- *Requires AV option board

Audio Connector:

- Unbalanced stereo (4 pair)
- RCA via breakout cable (included)

Dimensions:

- 6.60" L x 4.38" H (16.76 cm Lx 11.13 cm H)
- Full height/half length

Weight:

- ~ 227 g

Power Consumption:

- 11 W

Environment

- Operating Temp Range: 0■ to 40■ C
Storage Temp Range:-40■ to +75■ C
- Rel Humidity Operating: Between 5 % and 80 % (noncondensing)
Rel Humidity Non-Operating: 95 % RH (non-condensing); gradient
30% per hour