

Osprey 95-00186 PCI Analog/Composite/S-Video Capture Card/Audio/SimulStream (210)

- **Description:** Single channel analog audio/video selectable inputs
- **Format:** PCI 32-bit/5 Volt:
- **Video Input:** Composite S-Video
- **Video Connector:**
 - Composite (BNC x 1)
 - S-Video (mini-DIN)
- **Video Modes:**
 - NTSC/PAL 720 x 480 29.97
 - 30/i (NTSC) 852 x 480, 29.97
 - 30/i (NTSC Wide Screen)
 - 720 x 576 25/i (PAL)
 - Wide Screen Signaling (WSS)
- **Audio Input:** Unbalanced stereo
- **Audio Output:** Unbalanced stereo line (3.5 mm) Audio Connector: Unbalanced stereo (RCA x 2) Unbalanced (3.5 mini phono) stereo
- **Dimensions:** 5.08" L x 4.20" H (12.90 cm L x 10.67 cm H) Full-height/short
- **Weight:** ≈ 71 g
- **Power Consumption:** 2.45 W
- **Operating Temp Range:** 0° to 40° C
- **Non-Operating Temp Range:** -40° to +75° C
- **Rel Humidity Operating:** Between 5 % and 80 % (noncondensing) **Rel Humidity Non-Operating:** 95 % RH (non-condensing); gradient 30% per hour
- **Operating Altitude Range:** 0 to 3,048 meters (10,000 feet)
- **Non-Operating Altitude Range:** 0 to 15,240 meters (50,000 feet)
- **Warranty:** 1 year limited hardware warranty
- **Compliance:** CE, FCC, ROHS, WEEE
- **In the Box** Low-profile bracket Breakout cable