

# Osprey 95-00478 PCIe Analog/Composite/S-Video Capture Card/Audio/SimulStream(210e)

## Description:

- Single channel analog

## Format:

- PCIe (x 1):
- Slots: xl, x4, x8, or xl6
- PCIe 1.1

## Video Input:

- Composite
- S-Video

## Video Connector:

- Composite (BNC x 1) (RCA adapter included)
- S-Video (mini-DIN)

## Video Modes:

- NTSC/PAL
- 720x480 29.97, 30/i (NTSC)
- 852 x 480, 29.97, 30/i (NTSC Wide Screen)  
720 x 576 25/i (PAL)
- Wide Screen Signaling (WSS)

## Audio Input:

- Unbalanced stereo (3.5 mini phono)

## Audio Output:

- Unbalanced stereo line (3.5 mm)

## Audio Connector:

- Unbalanced stereo (RCA x 2)
- Unbalanced (3.5 mini phono) stereo

## Dimensions:

- 5.00" L x 2.71" H (12.70cmLx 6.88 cm H)
- Low profile/half length

## Weight:

- ~ 42 g

## Power Consumption:

- 2.62 W

## Operating Temp Range:

- 0■ to 40■ C

## Non-Operating Temp Range:

- -40■ to +75■ C

## Rel Humidity Operating:

- Between 5 % and 80 % (noncondensing)

## Rel Humidity Non-Operating:

- 95 % RH (non-condensing); gradient 30% per hour

**Operating Altitude Range:**

- 0 to 3,048 meters (10,000 feet)

**Non-Operating Altitude Range:**

- 0 to 15,240 meters (50,000 feet)