

Osprey 95-00489 Single 3G HD HDMI Input Capture Card with Embedded Audio (811e)

Description:

- One channel HDMI

Format:

- PCI Express (x 4):
- Slots: x 4, x 8, or x 16
PCIe 1.1

Video Input:

- 1x HDMI (non HDCP)

Video Connector:

- 1 x HDMI

Video Modes:

- 1080i 50, 59.94, 60
- 1080p 23.98, 24, 25, 29.97, 30, 50, 60
- 720p 23.98, 24, 25, 29.97, 50, 59.94, 60
- 720 x 480 29.97, 30/p
- 720 x 576 25, 50/p

Audio Input:

- HDMI 4 channels LCPM per input

Adapter:

- None

Available Drivers:

- Microsoft Windows
Linux

Dimensions:

- 6.6"L x 4.38" H (16.76cm x 11.13 cm)

Weight:

- = 113g

Power Consumption:

- 11.5 W

Operating Temp Range:

- 0■ to 40■ C

Non-Operating Temp Range:

- -40■ to +75■ C

Rel Humidity Operating:

- Between 5 % and 80 % (noncondensing)

Rel Humidity Non-Operating:

- 95 % RH (non-condensing); gradient 30% per hour

Operating Altitude Range:

- 0 to 3,048 meters (10,000 feet)

Non-Operating Altitude Range:

- 0 to 15,240 meters (50,000 feet)

System recommendations:

- High quality video capture requires a PCIe bus with direct access to the CPU