

Osprey 95-00490 Audio Expansion Option Card for 800e Series (800a)

Description:

- Audio Expansion Card for 800e Series video capture cards.

Format:

- PCI Express (x 1) for mechanical stability only. No bus connection required.

Audio Input:

- Balanced analog audio (2 stereo pair, 4 x XLR) Always available
Two additional pairs from list below
 - AES digital audio (2 stereo pair, 2 x XLR)
 - SPDIF digital audio (2 stereo pair, 2 x RCA)
 - Unbalanced analog audio (2 stereo pair, 4 x RCA)

Available Drivers:

- Automatically recognized by 800e capture card drivers. No additional drivers needed.

Dimensions:

- 6.60" L x 2.71" H (16.76cm L x 6.88 cm H)
- Low profile

Operating Temp Range:

- 0° to 40° C

Non-Operating Temp Range:

- -40° to +75° C

Rel Humidity Operating:

- Between 5 % and 80 % (noncondensing)

Rel Humidity Non-Operating:

- 95 % RH (non-condensing); gradient 30% per hour

Operating Altitude Range:

- 0 to 3,048 meters (10,000 feet)

Non-Operating Altitude Range:

- 0 to 15,240 meters (50,000 feet)

System recommendations:

- The 800a has no functionality unless attached to an Osprey 800e Series video capture card.