

# Osprey 97-21422 SDI to USB Video Capture with Loopout (VB-USL)

## Video Formats SDI:

- 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- 1920x1080i 50, 59.94, 60
- 1280x720p 25, 30, 50, 59.94, 60
- 576i 50 PAL
- 480i 60 NTSC

## Video Formats Out (YUV 422):

Frame rates 24, 25, 30, 50, 60

- 1920x1080
- 1680x1050
- 1440x900
- 1360x768
- 1280x1024
- 1280x800
- 1280x768
- 1280x720
- 1024x768
- 1024x576
- 960x540
- 856x480
- 800x600
- 768x576
- 720x576
- 720x480
- 640x480
- 640x360

## Video Input:

- 3G-SDI, SMPTE 259/292/424, YUV422
- SD, HD, 3G Auto Detect

## Audio Input:

- 2-Channel SDI Embedded Audio, 48kHz Sample Rate

## Interfaces:

- Full Size BNC
- Micro B USB 3.0 UVC/UAC Compliant

## Size:

- 4"x2.4"x0.65" (103x61x17mm)

## Weight:

- 0.251b (0.17kg)

## Power:

- 5V USB Powered; 4.5W max