

Osprey 96-02012 SDI/HDMI/Composite/Audio Input Talon G2 Encoder with Touch Display

Description

- 3 Channel Hardware Based Encoder with LCD Touch Display for easy functionality

Video Input

- 3G SMPTE 424M
- HD SMPTE 292M
- SD SMPTE 259M
- HDMI 1080P/60
- Composite (CVBS)

Video Connector

- Composite (RCA x 1)
- SDI(BNCx1)
- HDMI

Audio Input

- Unbalanced stereo
- Embedded SDI (1 stereo pair)
- Embedded HDMI (1 stereo pair)

Audio Connector

- Unbalanced stereo (3.5mm x 1)

Video Modes

- 1080p 23.98, 24, 25, 29.97, 30, 50, 59.95, 60
- 1080i 50, 59.94, 60
- 720p 23.98, 24, 25, 29.97, 50, 59.94, 60
- 720 x 480 29.97, 30/i (NTSC)
- 720 x 576 25/i (PAL)
- 720 x 576 25, 50/p

Encoding

- Video Encoding: H.264 RTMP, RTP, MPEG-2 TS UDP, .TS File
- Audio Encoding: AAC-LC & AAC-HE (32 to 320 kbps)

Closed Caption:

- Closed Captioning (EIA-608 & EIA-708) Type 1 ATSC Picture User Data is automatically embedded in the H.264 SEI per SCTE 128-1 standard*

LED indicators

- Power, Encoding, Signal Lock for SDI, HDMI, Composite

*Server and player must support closed caption data in order for the closed caption overlay to be available for display