

Osprey 97-41211 Scaling SDI to HDMI SHCSA-2 Converter

Input Video Formats SDI:

- 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- 1920x1080psf 23.98, 24, 25, 29.97, 30
- 1920x1080i 50, 59.94, 60
- 1280x720p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- SD PAL, NTSC

Output Video Formats HDMI:

- 1920x1080p 24, 25, 30, 50, 60
- 1920x1080i 50, 59.94, 60
- 1280x720p 24, 25, 30, 50, 59.94, 60
- SD PAL, NTSC

Output Video Formats AV:

- NTSC, PAL

HDMI Color Space and Precision:

- HDMI: YUV 4:2:2, YUV 4:4:4, RGB 4:4:4
- SDI: YUV 4:2:2

Video Input:

- 3G-SDI, SMPTE 259/292/424, YCbCr 4:2:2
- Alternate 3G-SDI (Failover)

Video Output:

- HDMI 1.3a
- CVBS (Composite)
- 3G-SDI Loopout (Primary SDI Input Only)

Audio Input:

- Embedded SDI, Analog Stereo, AES/EBU

Audio Output:

- Embedded HDMI, Analog Stereo, AES/EBU

Size:

- 5"x2.4"x0.95" (125.5x104x24.5mm)

Weight:

- 0.71b (0.30kg)

Power:

- 12V 6W max