

Osprey 95-00503 Quad 3G SDI All Channels I/O Capture Card (945)

Computer Interface

- PCI Express Gen2 x8

Power Consumption

- ~ 8.10W

Operating Temperature

- 0 to 40C

Weight

- 132g

Optional BNC Adapter Cables 34-03173

- Full Size BNC Female Jack to HD-BNC Male Plug
- Length 8" (including Connectors)
- 12G Rated Connectors and Belden 4855R

Connections

- 4 x bi-directional 3Gb/s SD/HD/3G-A (Micro HD BNC)

SDI Audio Inputs and Outputs

- Embedded 16 Channels (8 Stereo) per connection

Sync Input

- Tri-Sync or Black Burst (Micro HD BNC)

SD Video Standards

- 525i59.94 NTSC, 625i50 PAL

3G/HD Video Standards

- 720p50,59.94,60
- 1080p23.98,24,25,29.97,30,50,59.94,60
- 1080i50,59.94,60

SDI Compliance

- SMPTE 259M, SMPTE 292M, SMPTE 296M SMPTE 372M, SMPTE 425M, SMPTE 435, ITU-R BT.656 and ITU-R BT.601.

SDI Metadata Support

- CEA-608, CEA-708 for closed captioning

Audio Sampling

- Television standard sample rate of 48 kHz at 24-bit.

SDI Color Precision

- 8, 10, 12-bit RGB 4:4:4, YUV 4:4:4 and 4:2:2

Multiple Rate Support

- Auto Detect SD/HD/3G-A