

## HDMI® Extender over IP

### MVE-AHMPM-01NQ

HDMI over IP Kit (1 Transmitter and 1 Receiver)

### MVE-AHMPM-01NTQ

HDMI over IP (Transmitter)

### MVE-AHMPM-01NRQ

HDMI over IP (Receiver)



The MVE-AHMPM-01NQ HDMI Extender over IP extends the range of HDMI signals using an active transmitter and receiver to send video and audio over a single Cat5e/6 cable. The MVE-AHMPM-01NQ supports One-to-One, One-to-Many, and Many-to-Many installation via VLAN, as well as a cascading installation of multiple units for extended range.

### Features:


- Extends HDMI over one Cat5e/6 cable or IP network
- Supports One-to-One, One-to-Many, and Many-to-Many applications
- Supports cascaded installation
- IR Pass-through support (38kHz~56kHz)
- HDCP Compliant
- Transmitter (MVE-AHMPM-01NTQ) and receiver (MVE-AHMPM-01NRQ) also available separately



### Specifications:

| Model                       | Transmitter<br>MVE-AHMPM-01NTQ                       | Receiver<br>MVE-AHMPM-01NRQ |
|-----------------------------|--|-----------------------------|
| Maximum video resolution    | 1080p  |                             |
| Deep color                  | 24-bit   |                             |
| Video formats supported     | DTV/HDTV: 480i, 576i, 480p, 576p, 720p, 1080i, 1080p |                             |
| Range – 1080p               | Cat6   | 390ft (120m)                |
|                             | Cat5e  | 360ft (110m)                |
| IP addressing               | Static or dynamic                                    |                             |
| Default IP address (static) | 192.168.168.55                                       | 192.168.168.56              |
| Default MAC address         | 00:0b:78:00:60:01                                    | 00:0b:78:00:60:02           |
| IR frequency                | 38kHz~56kHz  |                             |
| Operating voltage           | 5VDC@1A  |                             |
| Power consumption           | 3W   |                             |
| Operating temperature       | 23°~95° F (-5°~35° C)                                |                             |
| Dimensions                  | 4 1/16" x 3 11/16" x 1" (104x94x25mm)                |                             |
| Weight                      | 7.8-oz (221g)  |                             |

### Sample Application – One-to-One:



For maximum cable length, see "Specifications"

HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.

### SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: [www.seco-larm.com](http://www.seco-larm.com) Email: [sales@seco-larm.com](mailto:sales@seco-larm.com)




Copyright 2016 © SECO-LARM U.S.A., Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®

PI\_MVE-AHMPM-01NQ\_160728.docx

## Sample Application – One-to-Many, Switch/Router:



## Sample Application – Many-to-Many, VLAN Switch:

