

Patton CL1214/S/EUI-2PK High Speed CopperLink Ethernet Extender (Local/Remote) Kit/RJ45 Line/POTS

CopperLink Line Interface	RJ-45 (pin 4 = ring; pin 5 = tip) BNC 75 Ω coax Terminal block, 2 position
CopperLink Line Modulation	DMT (Discrete Multi-Tone)
Ethernet Interface (x4)	8-position, shielded RJ-45. Auto-sensing 10/100Base-TX with half or full duplex operation.
Protocol	Transparent to high layer protocols: supports 802.1Q VLAN tagged or untagged frames. Transparent to IP Video schemes: fully transparent to such compression schemes as MPEG-4, H.264, and MJPEG.
Impulse Noise Protection Modes	Selectable fast and interleave modes
Target SNR Modes	6 dB and 9 dB
Management	8-position DIP switch
Monitoring	8 LEDs display Power, Link, Ethernet 1-4, Remote, and Local status.
Power Supply	External AC: 100-240 VAC
Compliance	FCC Part 15A, CE Mark, EMC Directive 89/336/EEC, Low-Voltage Directive 73/23/EEC
Environment	Temperature: 0 to 50°C Humidity: 5 to 95%, non-condensing Extended Temperature: -40 to 85°C (CL1214E/CC) Extended Humidity: 5 to 85%, condensing (CL1214E/CC)
Dimensions	6.22 W x 1.25 H x 4.75 L in. (15.74 W x 3.18 H x 12.07 L cm)
Weight	0.4 lbs (181 g)