

# Kramer C-FODM/FODM-164-BLACK Fiber Optic/DVI Hybrid Cable with Converters

## 164ft/Black

|                               |   |
|-------------------------------|---|
| COMPLIANCE WITH DVI STANDARD: | Supports DVI1.0 and DDC2B, fully implemented by fiber-optic communication, HDCP compatible. |
| EXTENSION LIMIT:              | 100m (328ft) for WXGA (1600 x 1200) @60Hz refresh rate.                                     |
| BANDWIDTH:                    | Supports UXGA at 60Hz or 1.65Gbps bandwidth per graphic channel.                            |
| HYBRID FIBER OPTIC CABLE:     | Riser jacket of retardant PVC using 4 strands.  |
| TENSILE LOAD:                 | 1,800N.   |
| MINIMUM BEND RADIUS:          | 15.4cm (6.1in).   |
| HUMIDITY:                     | 5% to 85%   |
| OUTER CABLE DIAMETER:         | 7.6mm (0.3in).  |
| DIMENSIONS:                   | 3.9cm x 1.54cm x 5.3cm (1.53in x 0.61in x 2.08in) W, D, H.                                  |
| POWER CONSUMPTION:            | 5V DC, <500mA.  |
| CLAMPING STRENGTH TO CABLE:   | 14kgf.  |
| TEMPERATURE:                  | Operating: 0° to 50°C (32° to 122°F), storage: -40° to 70°C (-40° to 158°F).                |