

ViewSonic VA2452SM 24 inch (23.6 inch Viewable) SuperClear MVA Monitor/6.5 ms/DisplayPort/DVI/VGA/Speakers

Display Size (in.):	24
Viewable Area (in.):	23.6
Panel Type:	MVA
Resolution:	1920 x 1080
Static Contrast Ratio:	3,000:1
Light Source:	LED
Brightness:	250 cd/m2
Colors:	16.7M
Response Time (Typical GTG):	7ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	40,000
Panel Surface:	3H Anti-glare, hard-coating
PC Resolution (max):	1920 x 1080
Mac® Resolution (max):	1920 x 1080
Internal Speakers:	1.5-watt (x2)
Eco Mode (Conserve):	15W
Eco Mode (optimized):	19W
Consumption (typical):	23W
Consumption (max):	30W
Voltage:	AC 100-240V (universal), 50-60Hz
Kensington Lock Slot:	1
Physical Controls:	1, 2, Down, Up, Power
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality)
Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%
VESA Compatible:	100 x 100 mm
Frequency Horizontal:	24~82kHz
Frequency Vertical:	50~75Hz
Analog Sync:	Separate Sync
Tilt (Forward/Back):	5° / 20°
Net (lbs):	8.6
Net Without Stand (lbs):	7.8
Gross (lbs):	11.1
Net (kg):	3.9
Net Without Stand (kg):	3.5
Gross (kg):	5
Packaging (in.):	24.3 x 16.1 x 4.9
Physical (in.):	22.2 x 16.6 x 7.8
Physical Without Stand (in.):	22.2 x 13.2 x 4.9
Packaging (mm):	616.0 x 409.0 x 124.0
Physical (mm):	563.0 x 421.7 x 196.8
Physical Without Stand (mm):	563.0 x 335.0 x 49.5
3.5mm Audio In(1), 3.5mm Audio Out(1), VGA(1), DVI-D(1), Display Port(1)	
Regulations:	cULus, Energy Star 7.0, FCC-B, ICES003, EPEAT Silver, UL-MX-CoC, Mexico Energy, CE, CB, RoHS, Reach, WEEE, TCO 6.0, Erp, UkrSPERO, EAC
PACKAGE CONTENTS:	VA2452Sm monitor, Power cable, VGA cable, Quick Start Guide

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	Three-year limited warranty on parts, labor and backlight
UPC:	766907810622